



COMMERCIAL

MULTISWITCHES - END-OF-LINE

MULTISWITCH LGT 5 WIRE END-OF-LINE 8 OUTPUTS

Product Code: DS/SMS5807NF



Light 07

passive



5 ... 65 MHz



4 x 950... 2200 MHz



- Passive terrestrial signal distribution in the frequency range of 5 ... 862 MHz
- Tap Loss for the terrestrial path between 20 and 25 dB (depends on the unit)
- Selection performance from > 26 dB for TERR-RF / SAT-IF and SAT-IF / TERR-RF
- Receiver/Receiver Isolation > 26 dB
- Short circuit proof, energy saving switch-mode power supplies with standby functionality
- LNB supply voltage selectable for Quattro or QUAD LNB

Specifications	DS/SMS5807NF
Inputs SAT-IF / TERR-RF	5, 4 / 1
Outputs / Subscribers	8
Tap Loss TERR-RF 5 ... 862 MHz	21 ... 16 dB
Tap Gain SAT-IF 950 ... 2200 MHz	-1 ... 5 dB
Output Level Max 950 ... 2200 MHz 35 dB IMA3/EN 60728-3	102 dB μ V
Isolation Receiver / Receiver TERR-RF / SAT-IF	\geq 26 dB
Mains Supply U~	100 ... 240 V / 47 ... 63 Hz
Power Consumption + LNB	7 W
Power Consumption Standby	< 1 W
LNB Supply Current Max	350 mA
Current Consumption from Each Receiver	10 mA
Ambient Temperature	- 20 ... + 50 °C
Dimensions (W x D x H mm)	132 x 56 x 220